

CLAIMS

I/we claim:

[c1] An apparatus for detecting characteristics of a microelectronic substrate having a first surface with first topographical features and a second surface facing opposite from the first surface and having second topographical features, the apparatus comprising:

- a support member configured to carry the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed; and
- a topographical feature detector positioned proximate to the support member and aligned with the first portion of the first surface of the microelectronic substrate, the topographical feature detector including a non-capacitive detection device configured to detect roughness characteristics of the first surface when the microelectronic substrate is carried by the support member.

[c2] The apparatus of claim 1 wherein the topographical feature detector is configured to:

- determine distances from a reference plane to a plurality of the first topographical features;
- select from the determined distances a minimum distance value;
- select from the determined distances a maximum distance value; and
- subtract the minimum distance value from the maximum distance value.

[c3] The apparatus of claim 1 wherein the second topographical features include conductive structures protruding from the second surface, and wherein the topographical feature detector is a first topographical feature detector, and wherein the apparatus further comprises a second topographical feature detector

positioned proximate to the support member and configured to detect a characteristic of the second topographical features when the microelectronic substrate is supported by the support member.

[c4] The apparatus of claim 1 wherein at least one of the topographical feature detector and the support member is movable relative to the other while the microelectronic substrate is carried by the support member.

[c5] The apparatus of claim 1 wherein the topographical feature detector includes of a first system configured to detect roughness features of microelectronic substrates having a first range of thicknesses, the first system being interchangeable with a second system configured to detect roughness features of microelectronic substrates having a second range of thicknesses, with a maximum thickness of the second range being greater than a maximum thickness of the first range.

[c6] The apparatus of claim 1 wherein the second topographical feature includes a solder bump, and wherein the apparatus further comprises a raised feature detector positioned proximate to the support member and configured to detect a characteristic of the solder bump.

[c7] The apparatus of claim 1 wherein the second topographical feature includes a gold bump, and wherein the apparatus further comprises a feature detector positioned proximate to the support member and configured to detect a characteristic of the gold bump.

[c8] The apparatus of claim 1, further comprising:
a first camera positioned proximate to the support member and configured to detect at least one of a position, a surface defect and a bridge of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support member; and

a second camera positioned proximate to the support member and configured to detect a height of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support member.

[c9] The apparatus of claim 1 wherein the support member has a contact surface with a plurality of apertures, the apertures being coupleable to a vacuum source to draw the microelectronic substrate into contact with the support member.

[c10] The apparatus of claim 1 wherein the support member has a generally ring-shaped contact surface, and wherein the first portion of the first surface of the microelectronic substrate is disposed annularly inwardly from the contact surface when the support member carries the microelectronic substrate.

[c11] The apparatus of claim 1 wherein the topographical feature detector includes a probe having a contact portion configured to contact the microelectronic substrate, the topographical feature detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the microelectronic substrate.

[c12] The apparatus of claim 1 wherein the topographical feature detector includes a radiation receiver positioned to receive radiation reflected from the microelectronic substrate, the topographical feature detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the microelectronic substrate.

[c13] The apparatus of claim 1 wherein the topography detector includes a laser beam emitter positioned to direct radiation toward the microelectronic substrate, the topography detector further including a laser beam receiver positioned to receive radiation reflected from the microelectronic substrate, the topography detector being configured to detect a roughness of the microelectronic substrate

based on measurements at a plurality of locations on the microelectronic substrate.

[c14] An apparatus for detecting characteristics of a microelectronic substrate having a first surface with first topographical features that do not include conductive connection structures, and a second surface facing opposite from the first surface and having second topographical features, the second topographical features including conductive structures protruding from the second surface, the apparatus comprising:

a support member configured to carry the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed; and

a topographical feature detector positioned proximate to the support member and aligned with the first portion of the first surface of the microelectronic substrate, the topographical feature detector including at least one of a contact probe and a radiation receiver positioned to detect characteristics of the first topographical features while the microelectronic substrate is carried by the support member without contacting the conductive structures protruding from the second portion of the second surface.

[c15] The apparatus of claim 14 wherein the topographical feature detector is configured to:

determine distances from a reference plane to a plurality of roughness features;

select from the determined distances a minimum distance value;

select from the determined distances a maximum distance value; and

subtract the minimum distance value from the maximum distance value.

[c16] The apparatus of claim 14 wherein the topographical feature detector is a first topographical feature detector, and wherein the apparatus further comprises

a second topographical feature detector positioned proximate to the support member and configured to detect a characteristic of the second topographical features when the microelectronic substrate is supported by the support member.

[c17]

An apparatus for detecting characteristics of a microelectronic substrate having a first surface with first topographical features that do not include conductive connection structures, and a second surface facing opposite from the first surface and having second topographical features, the second topographical features including conductive structures protruding from the second surface, the apparatus comprising:

- a support member configured to carry the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed;
- a first topographical feature detector positioned proximate to the support member and aligned with the first portion of the first surface of the microelectronic substrate when the microelectronic substrate is carried by the support member to detect characteristics of the first topographical features, the first topographical feature detector including at least one of a contact probe positioned to contact the first surface and a radiation receiver positioned to receive radiation reflected from the first surface; and
- a second topographical feature detector positioned proximate to the support member and aligned with the second portion of the second surface of the microelectronic substrate when the microelectronic substrate is carried by the support member to detect characteristics of the conductive structures protruding from the second surface.

[c18]

The apparatus of claim 17 wherein the first topographical feature detector is configured to:

- determine distances from a reference plane to a plurality of the first topographical features;

select from the determined distances a minimum distance value;
select from the determined distances a maximum distance value; and
subtract the minimum distance value from the maximum distance value to
determine a thickness variation for the microelectronic substrate.

[c19] The apparatus of claim 17 wherein the first topographical feature detector includes a first system configured to detect roughness features of microelectronic substrates having a first range of thicknesses, interchangeable with a second system configured to detect roughness features of microelectronic substrates having a second range of thicknesses different than the first range of thicknesses.

[c20] The apparatus of claim 17 wherein the second topographical feature detector includes:

a first camera positioned proximate to the support member and configured to detect at least one of a position, a surface defect and a bridge of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support member; and

a second camera positioned proximate to the support member and configured to detect a height of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support member.

[c21] The apparatus of claim 17 wherein the support member has a contact surface with a plurality of apertures, the apertures being coupleable to a vacuum source to draw the microelectronic substrate into contact with the support member.

[c22] The apparatus of claim 17 wherein the support member has a generally ring-shaped contact surface, and wherein the first portion of the first surface is disposed annularly inwardly from the contact surface when the support member carries the microelectronic substrate.

[c23] The apparatus of claim 17 wherein the first topographical feature detector includes a probe having a contact portion configured to contact the microelectronic substrate, the first topographical feature detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the microelectronic substrate.

[c24] The apparatus of claim 17 wherein the first topographical feature detector includes a radiation emitter positioned to direct radiation toward the microelectronic substrate, the first topographical feature detector further including a radiation receiver positioned to receive radiation reflected from the microelectronic substrate, the first topographical feature detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the microelectronic substrate.

[c25] An apparatus for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface and having raised conductive features, the apparatus comprising:

- a support member having a contact surface configured to contact the first surface of the microelectronic substrate, the support member being shaped to leave a first portion of the first surface exposed and a second portion of the second surface exposed when the microelectronic substrate contacts the support member;

- a roughness detector that includes a probe having a contact portion configured to contact the microelectronic substrate, the roughness detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the first surface of the microelectronic substrate; and

- an actuator coupled to at least one of the roughness detector and the support member to move at least one of the roughness detector and

the support member relative to the other while the support member supports the microelectronic substrate.

[c26] The apparatus of claim 25 wherein the contact surface has apertures coupleable to a vacuum source to draw the microelectronic substrate toward the support member.

[c27] The apparatus of claim 25 wherein the roughness detector is configured to:
determine distances from a reference plane to a plurality of the roughness features on the first surface of the microelectronic substrate;
select from the determined distances a minimum distance value;
select from the determined distances a maximum distance value; and
subtract the minimum distance value from the maximum distance value.

[c28] The apparatus of claim 25 wherein the roughness detector includes a first system configured to detect roughness features of microelectronic substrates having a first range of thicknesses, interchangeable with a second system configured to detect roughness features of microelectronic substrates having a second range of thicknesses different than the first range of thicknesses.

[c29] The apparatus of claim 25 wherein the raised conductive features include solder bumps and/or gold bumps, and wherein the apparatus further comprises a raised feature detector positioned proximate to the support member and configured to detect a characteristic of the solder bumps and/or gold bumps.

[c30] The apparatus of claim 25, further comprising:
a first camera positioned proximate to the support member and configured to detect at least one of a position, a surface defect and a bridge of at least one of the raised conductive features of the microelectronic substrate when the microelectronic substrate is supported by the support member; and

a second camera positioned proximate to the support member and configured to detect a height of at least one of the raised conductive features of the microelectronic substrate when the microelectronic substrate is supported by the support member.

[c31] The apparatus of claim 25 wherein the support member has a generally ring-shaped contact surface, and wherein the first portion of the first surface is disposed annularly inwardly from the contact surface when the support member carries the microelectronic substrate.

[c32] An apparatus for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface and having raised conductive features, the apparatus comprising:

a support member having a contact surface configured to contact the first surface of the microelectronic substrate, the support member being shaped to leave a first portion of the first surface and a second portion of the second surface exposed when the microelectronic substrate contacts the support member;

a roughness detector that includes a radiation receiver positioned to receive radiation reflected from the first surface of the microelectronic substrate, the roughness detector being configured to detect a roughness of the microelectronic substrate based on measurements at a plurality of locations on the first surface of the microelectronic substrate; and

an actuator coupled to at least one of the roughness detector and the support member to move at least one of the roughness detector and the support member relative to the other while the support member supports the microelectronic substrate.

[c33] The apparatus of claim 32 wherein the contact surface has apertures coupleable to a vacuum source to draw the microelectronic substrate into contact with the support member.

[c34] The apparatus of claim 32 wherein the roughness detector includes a radiation emitter is configured to emit laser radiation and a radiation receiver configured to receive laser radiation.

[c35] The apparatus of claim 32 wherein the roughness detector is configured to:
determine distances from a reference plane to a plurality of the roughness features on the first surface of the microelectronic substrate;
select from the determined distances a minimum distance value;
select from the determined distances a maximum distance value; and
subtract the minimum distance value from the maximum distance value.

[c36] The apparatus of claim 32, further comprising:
a first camera positioned proximate to the support member and configured to detect at least one of a position, a surface defect and a bridge of at least one of the raised conductive features of the microelectronic substrate when the microelectronic substrate is supported by the support member; and
a second camera positioned proximate to the support member and configured to detect a height of at least one of the raised conductive features of the microelectronic substrate when the microelectronic substrate is supported by the support member.

[c37] The apparatus of claim 32 wherein the support member has a generally ring-shaped contact surface, and wherein the first portion of the first surface is disposed annularly inwardly from the contact surface when the support member carries the microelectronic substrate.

1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2

detecting characteristics of surface roughness features on a surface and having raised support member;
 on the support member contact the first surface a first portion of the of the second surface positioned proximate to or being and aligned with microelectronic substrate carried by the support member or including at least one first surface, and a reflection reflected from the first of the roughness detector to the other while the support member, and vertically positioned proximate to substrate to detect a surface characteristic of the microelectronic substrate detector positioned proximate to the microelectronic substrate to detect features relative to the substrate is carried by

- g and a
electron
the su

[c39] The apparatus of claim 38 wherein the raised conductive features include solder bumps and/or gold bumps, and wherein the first and second feature detectors are configured to detect characteristics of the solder bumps and/or gold bumps.

[c40] An apparatus for detecting characteristics of a microelectronic substrate having a first surface with first topographical features that include roughness elements, and a second surface facing opposite from the first surface and having second topographical features that include raised conductive structures, the apparatus comprising:

support means configured to carry the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed;

first topography detection means positioned proximate to the support member and aligned with the first portion of the first surface of the microelectronic substrate to detect at least one or a roughness and a thickness variation of the first surface when the microelectronic substrate is carried by the support member, the first topography detection means including at least one of a contact probe positioned to contact the first surface and a radiation receiver positioned to receive radiation reflected from the first surface; and

second topography detection means positioned proximate to the support member and aligned with the second portion of the second surface to detect a characteristic of the raised conductive structures when the microelectronic substrate is carried by the support means.

[c41] The apparatus of claim 40, further comprising actuator means operatively coupled to at least one of the first topography detection means and the support means to move at least one of the first topography detection means and the support means relative to the other while the microelectronic substrate is carried by the support means.

[c42] The apparatus of claim 40 wherein the first topography detection means is configured to:

determine distances from a reference plane to a plurality of roughness features of the microelectronic substrate;
select from the determined distances a minimum distance value;
select from the determined distances a maximum distance value; and
subtract the minimum distance value from the maximum distance value.

[c43] The apparatus of claim 40 wherein the first topography detection means includes a first system configured to detect roughness features of microelectronic substrates having a first range of thicknesses, interchangeable with a second system configured to detect roughness features of microelectronic substrates having a second range of thicknesses different than the first range of thicknesses.

[c44] The apparatus of claim 40 wherein the second topography detection means includes:

a first camera positioned proximate to the support means and configured to detect at least one of a position, a surface defect and a bridge of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support means; and
a second camera positioned proximate to the support means and configured to detect a height of at least one of the second topographical features of the microelectronic substrate when the microelectronic substrate is supported by the support means.

[c45] The apparatus of claim 38 wherein the support means has a contact surface with a plurality of apertures, the apertures being coupleable to a vacuum source to draw the microelectronic substrate into contact with the support member.

[c46] The apparatus of claim 38 wherein the support means has a generally ring-shaped contact surface, and wherein the first portion of the first surface is disposed annularly inwardly from the contact surface when the support member carries the microelectronic substrate.

[c47] The apparatus of claim 38 wherein the first topography detection means includes a probe having a contact portion configured to contact the first surface of the microelectronic substrate, the first topography detection means being configured to detect a roughness of the first surface based on measurements at a plurality of locations on the first surface.

[c48] The apparatus of claim 38 wherein the first topography detection means includes a radiation receiver positioned to receive radiation reflected from the first surface, the first topography detection means being configured to detect a roughness of the first surface based on measurements at a plurality of locations on the first surface.

[c49] A method for processing a microelectronic substrate, comprising:
forming first topographical features on or in a first surface of the microelectronic substrate, the first topographical features including roughness features but not including electrical connection structures offset from the first surface;
forming second topographical features on or in a second surface of the microelectronic substrate facing opposite from the first surface, the second topographical features including conductive structures protruding from the second surface;
supporting the microelectronic substrate while a first portion of the first surface is exposed and a second portion of the second surface is exposed; and
detecting a characteristic of the first topographical features by positioning a topographical detection device at least proximate to the first portion

of the first surface and activating the topographical detection device while the first portion of the first surface is exposed and while the second portion of the second surface is exposed with the conductive structures protruding from the second surface.

[c50] The method of claim 49 wherein detecting a characteristic of the first topographical features includes detecting a roughness of the first portion of the first surface by positioning a roughness detection device at least proximate to the first portion and activating the roughness detection device while the first portion of the first surface is exposed.

[c51] The method of claim 49 wherein detecting a characteristic of the first portion includes receiving radiation reflected from the first portion.

[c52] The method of claim 49 wherein supporting the microelectronic substrate includes carrying the microelectronic substrate with a support member, and wherein the method further comprises detecting a characteristic of at least one of the second topographical features while carrying the microelectronic substrate with the support member.

[c53] The method of claim 49, further comprising moving at least one of the microelectronic substrate and the topographical detection device relative to the other while the first portion of the first surface is exposed.

[c54] The method of claim 49, further comprising determining a thickness variation for the microelectronic substrate by:

- establishing a reference plane;
- determining distances from the reference plane to a plurality of roughness features of the first surface;
- selecting from the determined distances a minimum distance value;
- selecting from the determined distances a maximum distance value; and
- subtracting the minimum distance value from the maximum distance value.

[c55] The method of claim 49 wherein supporting the microelectronic substrate includes positioning the microelectronic substrate on a generally ring-shaped support surface with the first portion of the first surface positioned radially inward from the support surface.

[c56] The method of claim 49 wherein supporting the microelectronic substrate includes forcing the microelectronic substrate into contact with a support member.

[c57] The method of claim 47 wherein supporting the microelectronic substrate includes applying a vacuum to the microelectronic substrate to draw the microelectronic substrate into contact with a support member.

[c58] The method of claim 47, further comprising detecting at least one of a position, a surface defect, and a bridge of at least one of the second topographical features while supporting the microelectronic substrate with the first portion of the first surface exposed and the second portion of the second surface exposed.

[c59] The method of claim 49, further comprising detecting a height of at least one of the second topographical features of the microelectronic substrate while supporting the microelectronic substrate with the first portion of the first surface exposed and the second portion of the second surface exposed.

[c60] The method of claim 49, further comprising detecting a characteristic of at least one of the second topographical features by directing laser radiation toward the microelectronic substrate and receiving radiation reflected from the microelectronic substrate while the first portion of the first surface is exposed and the second portion of the second surface is exposed.

[c61] The method of claim 49, further comprising removing material from the first surface of the microelectronic before, after, or both before and after detecting a characteristic of the first topographical features.

[c62]

The method of claim 49, further comprising:

removing a first portion of material from the first surface of the microelectronic substrate prior to detecting a characteristic of the first topographical features; and

removing a second portion of material from the first surface of the microelectronic substrate after detecting a characteristic of the first topographical features.

[c63]

A method for detecting characteristics of a microelectronic substrate having a first surface with first topographical features that do not include conductive connection structures, and a second surface facing opposite from the first surface and having second topographical features, the method comprising:

supporting the microelectronic substrate while at least a first portion of the first surface is exposed and at least a second portion of the second surface is exposed; and

detecting a roughness of the first surface by positioning a topographical detection device at least proximate to the first topographical features of the first surface and activating the topographical detection device to receive feedback from the first topographical features while the first portion of the first surface and the second portion of the second surface are exposed.

[c64]

The method of claim 63 wherein detecting a roughness of the first surface includes contacting a probe with the first portion of the first surface to determine a roughness of the first portion.

[c65]

The method of claim 63 wherein detecting a roughness of the first surface includes receiving radiation reflected from the first portion.

[c66]

The method of claim 63 wherein supporting the microelectronic substrate includes carrying the microelectronic substrate with a support member, and wherein the method further comprises detecting a characteristic of at least one of

the second topographical features while carrying the microelectronic substrate with the support member.

[c67] The method of claim 63, further comprising moving at least one of the microelectronic substrate and the topographical detection device relative to the other while the first portion of the first surface is exposed.

[c68] The method of claim 63, further comprising determining a thickness variation for the microelectronic substrate by:

establishing a reference plane;

determining distances from the reference plane to a plurality of roughness features of the first surface;

selecting from the determined distances a minimum distance value;

selecting from the determined distances a maximum distance value; and

subtracting the minimum distance value from the maximum distance value.

[c69] The method of claim 63 wherein supporting the microelectronic substrate includes positioning the microelectronic substrate on a generally ring-shaped support surface with the first portion of the first surface positioned radially inwardly from the support surface.

[c70] The method of claim 63 wherein supporting the microelectronic substrate includes forcing the microelectronic substrate into contact with a support member.

[c71] The method of claim 63 wherein supporting the microelectronic substrate includes applying a vacuum to the microelectronic substrate to draw the microelectronic substrate into contact with a support member.

[c72] The method of claim 63, further comprising detecting a characteristic of at least one of the second topographical features while supporting the microelectronic substrate with the first portion of the first surface exposed and the second portion of the second surface exposed.

[c73] The method of claim 63, further comprising detecting at least one of a position, a surface defect, and a bridge of at least one of the second topographical features while supporting the microelectronic substrate with the first portion of the first surface exposed and the second portion of the second surface exposed.

[c74] The method of claim 63, further comprising detecting a height of at least one of the second topographical features of the microelectronic substrate while supporting the microelectronic substrate with the first portion of the first surface exposed and the second portion of the second surface exposed.

[c75] The method of claim 63, further comprising detecting a characteristic of at least one of the second topographical features by directing laser radiation toward the microelectronic substrate and receiving radiation reflected from the microelectronic substrate while the first portion of the first surface is exposed and the second portion of the second surface is exposed.

[c76] The method of claim 63, further comprising removing material from the first surface of the microelectronic before, after, or both before and after detecting a characteristic of the first topographical features.

[c77] The method of claim 63, further comprising:
removing a first portion of material from the first surface of the microelectronic substrate prior to detecting a characteristic of the first topographical features; and
removing a second portion of material from the first surface of the microelectronic substrate after detecting a characteristic of the first topographical features.

[c78] A method in a computer for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface, the method comprising:

receiving a plurality of measurements for distances between a reference plane and a corresponding plurality of the roughness features of the first surface of the microelectronic substrate;
selecting a minimum distance value from the plurality of distance values;
selecting a maximum distance value from the plurality of distance values;
and
determining a thickness variation for the microelectronic substrate by subtracting the minimum distance value from the maximum distance value.

[c79] The method of claim 78, further comprising determining a roughness value for the microelectronic substrate from the plurality of distance measurements.

[c80] The method of claim 78 wherein receiving the plurality of distance measurements includes receiving a plurality of distance measurements made by a probe that contacts the microelectronic substrate.

[c81] The method of claim 78 wherein receiving the plurality of distance measurements includes receiving a plurality of distance measurements from a device that receives radiation reflected from the microelectronic substrate.

[c82] A method for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface and having protruding conductive features, the method comprising:

supporting the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed; and

detecting a roughness of the first portion of the first surface by contacting a probe with the first portion and moving at least one of the probe and the microelectronic substrate relative to the other while the first

portion of the first surface is exposed and the second portion of the second surface is exposed.

[c83] The method of claim 82 wherein supporting the microelectronic substrate includes carrying the microelectronic substrate with a support member, and wherein the method further comprises detecting a characteristic of at least one of the protruding conductive features while carrying the microelectronic substrate with the support member.

[c84] The method of claim 82, further comprising determining a thickness variation for the microelectronic substrate by:

establishing a reference plane;
determining distances from the reference plane to a plurality of roughness features of the first surface;
selecting from the determined distances a minimum distance value;
selecting from the determined distances a maximum distance value; and
subtracting the minimum distance value from the maximum distance value.

[c85] The method of claim 82 wherein supporting the microelectronic substrate includes positioning the microelectronic substrate on a generally ring-shaped support surface with the first portion of the first surface positioned radially inwardly from the support surface.

[c86] The method of claim 82 wherein supporting the microelectronic substrate includes applying a vacuum to the microelectronic substrate to draw the microelectronic substrate into contact with a support member.

[c87] The method of claim 82, further comprising:
removing a first portion of material from the first surface of the microelectronic substrate prior to detecting a characteristic of the first topographical features; and

removing a second portion of material from the first surface of the microelectronic substrate after detecting a characteristic of the first topographical features.

[c88]

A method for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface and having protruding conductive features, the method comprising:

supporting the microelectronic substrate with a first portion of the first surface exposed and a second portion of the second surface exposed; and

detecting a roughness of the first portion of the first surface by directing radiation toward the microelectronic substrate, receiving radiation reflected from the microelectronic substrate at a radiation receiver, and moving at least one of the receiver and the microelectronic substrate relative to the other while the first portion of the first surface is exposed and the second portion of the second surface is exposed.

[c89]

The method of claim 88 wherein supporting the microelectronic substrate includes carrying the microelectronic substrate with a support member, and wherein the method further comprises detecting a characteristic of at least one of the protruding conductive features while carrying the microelectronic substrate with the support member.

[c90]

The method of claim 88, further comprising determining a thickness variation for the microelectronic substrate by:

establishing a reference plane;

determining distances from the reference plane to plurality of roughness features of the first surface;

selecting from the determined distances a minimum distance value;

selecting from the determined distances a maximum distance value; and
subtracting the minimum distance value from the maximum distance value.

[c91] The method of claim 88 wherein supporting the microelectronic substrate includes positioning the microelectronic substrate on a generally ring-shaped support surface with the first portion of the first surface positioned radially inwardly from the support surface.

[c92] The method of claim 88 wherein supporting the microelectronic substrate includes applying a vacuum to the microelectronic substrate to draw the microelectronic substrate into contact with a support member.

[c93] The method of claim 88, further comprising:
removing a first portion of material from the first surface of the microelectronic substrate prior to detecting a roughness of the first surface; and
removing a second portion of material from the first surface of the microelectronic substrate after detecting a roughness of the first surface.

[c94] A method for detecting characteristics of a microelectronic substrate having a first surface with roughness features and a second surface facing opposite from the first surface and having protruding conductive features, the method comprising:

supporting the microelectronic substrate by carrying the microelectronic substrate with a support member while a first portion of the first surface is exposed and a second portion of the second surface is exposed;

detecting a roughness of the first portion of the first surface by positioning a roughness detection device at least proximate to the first portion and moving at least one of the detection device and the microelectronic substrate relative to the other while the first portion

of the first surface is exposed and the second portion of the second surface is exposed; and
detecting a characteristic of at least one of the protruding conductive features while the microelectronic substrate is carried by the support member.

[c95] The method of claim 94, further comprising determining a thickness variation for the microelectronic substrate by:

establishing a reference plane;
determining distances from the reference plane to a plurality of roughness features of the first surface;
selecting from the determined distances a minimum distance value;
selecting from the determined distances a maximum distance value; and
subtracting the minimum distance value from the maximum distance value.

[c96] The method of claim 94, further comprising detecting a characteristic of at least one of the protruding conductive features with a camera while the first portion of the first surface is exposed and the second portion of the second surface is exposed.

[c97] The method of claim 94, further comprising:
removing a first portion of material from the first surface of the microelectronic substrate prior to detecting a roughness of the first surface; and
removing a second portion of material from the first surface of the microelectronic substrate after detecting a roughness of the first surface.